

## عنوان مقاله:

Aniline adsorption on the surface of a BN nanotube: Computational study

## محل انتشار:

فصلنامه شیمی نوین، دوره 1، شماره 1 (سال: 1393)

تعداد صفحات اصل مقاله: 9

## نویسندگان:

Maziar Noei - Department of Chemistry, College of Chemical engineering, Mahshahr Branch, Islamic Azad University, Mahshahr, Iran

Shima Ebadola - Department of Chemistry, College of chemistry Yadegar Emam Khomeini Branch, Tehran, Iran

Ali Akbar Salari - Department of Chemistry, College of chemistry Yadegar Emam Khomeini Branch, Tehran, Iran

## خلاصه مقاله:

Electrical sensitivity of a boron nitride nanotube (BNNT) was examined toward aniline ( $C_6H_5NH_2$ ) molecule by using density functional theory (DFT) calculations at the B3LYP/6-31 G (d) level, and it was found that the adsorption energy ( $E_{ad}$ ) of aniline on the pristine nanotubes is about -19.03 kcal/mol. But when nanotube has been doped with Si and Al atoms, the adsorption energy of aniline molecule was increase. Calculation showed that when the nanotube is doping by Al, the adsorption energy is about -27.73 kcal/mol and also the amount of HOMO/LUMO energy gap ( $E_g$ ) will reduce significantly. Boron nitride nanotube is a suitable adsorbent for aniline and can be used in separation processes aniline. It is seem that nanotube (BNNT) is a suitable semiconductor after doping, and the doped BNNT in the presence of aniline an electrical signal is generating directly and therefore can potentially be used for aniline sensors.

## کلمات کلیدی:

Sensor, Nanotube, DFT, Aniline

## لینک ثابت مقاله در پایگاه سیویلیکا:

<https://civilica.com/doc/792608>

